

Compact, full-featured DIN-rail power system

The Micropack System is convection cooled, designed for less power hungry applications, but still with system functionality options to match any requirements. Use as stand alone or in a flexible off the shelf configurable system.

The Micropack Power System extends your network one step further. With load ranges typically between 120W and 1000W, and in 12, 24 and 48V options, the system is perfect for a great variety of applications.



Micropack Rectifiers

12V_{DC}/120W, 24-30V_{DC}/240W & 48V_{DC}/250W

DOCUMENT NO: 241120.123xx.DS3 - v2

INDUSTRY APPLICATIONS

Telecom

- LTE/femto cells
- Small base stations / repeaters
- Fixed & mobile broadband
- FTTx

Power utilities

- Control & protection
- Scada
- Communication

Railway infrastructure

- Control & protection
- Signaling

Various other applications in demanding industries like Marine, Oil & Gas, process etc.



Micropack system



Compact controller

KEY FEATURES

- ü Convection cooled – inaudible
- ü Accepts 85 – 300 V_{AC/DC} input
- ü 12, 24-30, 48 V_{DC} output versions
- ü NiCad support for 12 and 24V_{DC}
- ü Quick-trip pulse to help open load MCB
- ü Pot-meter voltage adjustment for standalone
- ü Module alarm relay contact for basic monitoring without controller
- ü Active current sharing
- ü Comprehensive monitoring and control when used with controller:
 - Remote/local connection through Ethernet
 - Webpages and SNMP support
 - Monitoring of rectifier temperature, input voltage and output current
- ü Modular approach in DIN-rail mountable back planes
- ü Off-the-shelf delivery

See reverse side for specifications

Micropack Rectifiers



12V_{DC}/120W, 24-30V_{DC}/240W & 48V_{DC}/250W

Model	12V / 120W	24V / 240W	48V / 250W
Part number	241120.300	241120.200	241120.100
INPUT DATA			
Voltage range	85 - 300 V _{AC/DC} ¹⁾		
Voltage range (nominal)	130 - 275 V _{AC/DC}	185 - 275 V _{AC/DC} ¹⁾	
Frequency	0 - 66 Hz ¹⁾		
Maximum current, 230V input / overall (boost)	0.6 A / 2.0 A	1.2 A / 2.0 A	1.2 A / 1.9 A
Maximum earth leakage current	2.0 mA (@ 250V _{AC} /50Hz)		
Power Factor	0.97 (@ 70 - 100 % load)	0.98 (@ 55 - 100 % load)	0.98 (@ 50 - 100 % load)
THD (@ 230 V _{AC})	< 5 % (@ 80 - 100 % load)	< 5 % (@ 50 - 100 % load)	< 5 % (@ 50 - 100 % load)
Protection	Varistor for transient protection, fuse in both lines (2x 2.0 A), shutdown above 300 V _{AC/DC}		
OUTPUT DATA			
Default voltage	13.6 V _{DC}	27.2 V _{DC}	53.5 V _{DC}
Voltage range	10.7 - 18.0 V _{DC}	21.5 - 36 V _{DC}	43.5 - 57.6 V _{DC}
Voltage range without controller	10.7 - 15.0 V _{DC}	21.5 - 30 V _{DC}	43.5 - 57.6 V _{DC}
# Pb cell supported (1.8 - 2.4 V _{DC} /cell)	6 - 7	12 - 15	24
# NiCad cell supported (1.05 - 1.65 V _{DC} /cell)	10 - 11 ²⁾	20 - 22 ²⁾	-
Max power, nominal / 60s boost	120 W / 160 W	240 W / 315 W	250 W / -
Max current, @12/24/48V _{DC} / boost / QT ³⁾	10 A / 15 A / 55 A	10 A / 15 A / 55 A	5 A / - / -
Current sharing	±5% of maximum current from 10 to 100% load		
Static voltage regulation	±0.5% from 10% to 100% load and nominal input		
Dynamic voltage regulation	± 5 % < 10ms, load step 10% to 90% or opposite at nominal output voltage		
Hold-up time, default voltage and full power	20 ms, V _{OUT} > 10.7 V _{DC}	20 ms, V _{OUT} > 21.5 V _{DC}	20 ms, V _{OUT} > 43 V _{DC}
Rippel and noise, 30 MHz b.w. / psophometric	< 200 mV _{PP} / 5 mV _{RMS}	< 200 mV _{PP} / 5 mV _{RMS}	< 150 mV _{PP} / 2 mV _{RMS}
Protection	Overvoltage shutdown, short circuit proof, high temperature, hot plug-in inrush current limiting, fuse		
OTHER SPECIFICATIONS			
Efficiency @ nominal input/output, peak/range	89.5% / >88%, 50-100% load	93.0% / >92%, 50-100% load	93.6% / >93%, 50-100% load
Isolation	3.0 kV _{AC} – input and output, 1.5 kV _{AC} – input earth, 0.5 kV _{DC} – output earth		
Alarms: Red LED 'on'	Low mains shutdown, High and low temperature shutdown, Rectifier Failure, Overvoltage shutdown on output, Fan failure, Low voltage alarm, CAN bus failure		
Warnings: Yellow LED 'on'	Rectifier in power derate mode, Remote battery current limit activated, Input voltage out of range, flashing at overvoltage		
Normal (module running): Green LED 'on'			
Alarm output (isolated)	NO (+positive terminal), COM (-negative terminal). 60 V / 100 mA max		
MTBF (Telcordia SR-332 Issue I method III (a))	>480 000h (@T _{AMBIENT} = 25°C)	>480 000h (@T _{AMBIENT} = 25°C)	>500 000h (@T _{AMBIENT} = 25°C)
Operating temperature (5 - 95% RH non-cond.)	-40 to +70°C [-40 — +158°F]	-40 to +60°C [-40 to +142°F]	-40 to +75°C [-40 to +167°F]
Output power de-rates above temp / to	+55°C / 50W @ +70°C	+45°C / 80W @ +60°C	+55°C / 140W @ +75°C
Storage temperature	-40 to +85°C (-40 to +185°F), humidity 0 - 99% RH non-condensing		
Dimensions[WxHxD] / Weight	39.0 x 88.5 x 149mm [1.54 x 3.48 x 5.87"] / 0.5 kg [1.1 lbs]		
DESIGN STANDARDS			
Electrical safety	UL 60950-1, EN 60950-1, CSA 22.2		
EMC	ETSI EN 300 386 V.1.3.2 EN 61000-6-1 / -2 / -3 / -4 / -5 ⁴⁾		
Mains Harmonics	EN 61000-3-2		
Environment	ETSI EN 300 019: 2-1 (Class 1.2), 2-2 (Class 2.3) & 2-3 (Class 3.2) ETSI EN 300 132-2 2002/95/EC (RoHS) & 2002/96/EC (WEEE)		
Marine compliance (EMC class B with AC filter)	DnV Rules for Classification of Ships, High Speed & Light Craft and DnV Offshore Standards		
¹⁾ DC support for 241120.200 with primary FW 404088.009 (from HW revision 1.2) and 241120.100 from HW revision 2 ²⁾ 11/22 cells with max boost voltage 1.636 V _{DC} /cell ³⁾ Quick-Trip function, if V _{OUT} = 5 V _{DC} a 35 ms current pulse is generated to help trip fuse/MCB on short circuited branch ⁴⁾ Only 12V and 24V			